

JF100M許容スパン表 (S造)

普通コンクリート

鉄筋コンクリート単重 $\rho = 24$ (kN/m³)

| スラブ厚 S (mm) | 許 容 ス パ ン : L (mm) | | | | | | |
|----------------------------|--------------------|-----------|-----------|-----------|-----------|-----------|-------|
| | JF100M-07 | JF100M-08 | JF100M-10 | JF100M-12 | JF100M-14 | JF100M-16 | |
| | Z= | 37.3 | 42.6 | 46.6 | 56.2 | 65.9 | 75.6 |
| | I= | 250 | 284 | 352 | 417 | 482 | 545 |
| 120 | | 3,360 | 3,740 | 3,990 | 4,310 | 4,500 | 4,670 |
| 125 | | 3,360 | 3,710 | 3,960 | 4,270 | 4,460 | 4,630 |
| 130 | | 3,360 | 3,680 | 3,930 | 4,240 | 4,430 | 4,590 |
| 135 | | 3,360 | 3,650 | 3,900 | 4,210 | 4,390 | 4,560 |
| 140 | | 3,360 | 3,630 | 3,870 | 4,180 | 4,360 | 4,520 |
| 145 | | 3,360 | 3,600 | 3,840 | 4,150 | 4,330 | 4,490 |
| 150 | | 3,360 | 3,570 | 3,810 | 4,120 | 4,300 | 4,460 |
| 155 | | 3,330 | 3,550 | 3,790 | 4,090 | 4,270 | 4,430 |
| 160 | | 3,310 | 3,520 | 3,760 | 4,060 | 4,240 | 4,400 |
| 165 | | 3,290 | 3,500 | 3,730 | 4,030 | 4,210 | 4,370 |
| 170 | | 3,270 | 3,480 | 3,710 | 4,000 | 4,180 | 4,340 |
| 175 | | 3,250 | 3,450 | 3,690 | 3,980 | 4,160 | 4,310 |
| 180 | | 3,230 | 3,430 | 3,660 | 3,950 | 4,130 | 4,290 |
| 185 | | 3,210 | 3,410 | 3,640 | 3,930 | 4,110 | 4,260 |
| 190 | | 3,190 | 3,390 | 3,620 | 3,910 | 4,080 | 4,230 |
| 195 | | 3,170 | 3,370 | 3,600 | 3,880 | 4,060 | 4,210 |
| 200 | | 3,150 | 3,350 | 3,580 | 3,860 | 4,030 | 4,180 |
| 205 | | 3,130 | 3,330 | 3,550 | 3,840 | 4,010 | 4,160 |
| 210 | | 3,110 | 3,310 | 3,530 | 3,820 | 3,990 | 4,140 |
| 215 | | 3,100 | 3,290 | 3,520 | 3,790 | 3,960 | 4,110 |
| 220 | | 3,080 | 3,270 | 3,500 | 3,770 | 3,940 | 4,090 |
| 225 | | 3,060 | 3,260 | 3,480 | 3,750 | 3,920 | 4,070 |
| 230 | | 3,050 | 3,240 | 3,460 | 3,730 | 3,900 | 4,050 |
| 235 | | 3,030 | 3,220 | 3,440 | 3,710 | 3,880 | 4,030 |
| 240 | | 3,010 | 3,210 | 3,420 | 3,700 | 3,860 | 4,010 |
| 245 | | 3,000 | 3,190 | 3,400 | 3,680 | 3,840 | 3,990 |
| 250 | | 2,980 | 3,180 | 3,380 | 3,660 | 3,820 | 3,970 |
| 255 | | 2,970 | 3,160 | 3,350 | 3,640 | 3,810 | 3,950 |
| 260 | | 2,960 | 3,140 | 3,330 | 3,620 | 3,790 | 3,930 |
| 265 | | 2,940 | 3,130 | 3,300 | 3,610 | 3,770 | 3,910 |
| 270 | | 2,930 | 3,120 | 3,280 | 3,590 | 3,750 | 3,890 |
| 275 | | 2,920 | 3,100 | 3,250 | 3,560 | 3,740 | 3,880 |
| 280 | | 2,900 | 3,090 | 3,230 | 3,540 | 3,720 | 3,860 |
| 285 | | 2,880 | 3,070 | 3,210 | 3,510 | 3,700 | 3,840 |
| 290 | | 2,860 | 3,050 | 3,180 | 3,490 | 3,690 | 3,830 |
| 295 | | 2,840 | 3,030 | 3,160 | 3,470 | 3,670 | 3,810 |
| 300 | | 2,820 | 3,010 | 3,140 | 3,440 | 3,650 | 3,790 |
| 重量(Z12)[N/m ²] | | 133 | 151 | 188 | 223 | 258 | 294 |

| | | |
|--------|-------|--------------------|
| ヤング係数; | 205 | kN/mm ² |
| 撓み係数; | 180 | |
| 施工荷重; | 1,470 | N/m ² |
| 許容応力; | 235 | N/mm ² |

※なお、 部はたわみで決定する箇所を示す。
※赤文字部は、計算に依らず、デッキの最大スパンを示す。

JF100M中間サポート使用許容スパン表 (S造)

普通コンクリート

鉄筋コンクリート単重 $\rho = 24$ (kN/m³)

| スラブ厚 S (mm) | 許容スパン : L (mm) | | | | | |
|----------------|----------------|-----------|-----------|-----------|-----------|-----------|
| | JF100M-07 | JF100M-08 | JF100M-10 | JF100M-12 | JF100M-14 | JF100M-16 |
| | Z= | 42.6 | 46.6 | 56.2 | 65.9 | 75.6 |
| | I= | 284 | 352 | 417 | 482 | 545 |
| 120 | 4,370 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 125 | 4,250 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 130 | 4,140 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 135 | 4,040 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 140 | 3,940 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 145 | 3,850 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 150 | 3,760 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 155 | 3,680 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 160 | 3,600 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 165 | 3,520 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 170 | 3,440 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 175 | 3,370 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 180 | 3,300 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 185 | 3,240 | 4,850 | 4,900 | 4,900 | 4,900 | 4,900 |
| 190 | 3,180 | 4,750 | 4,900 | 4,900 | 4,900 | 4,900 |
| 195 | 3,110 | 4,660 | 4,900 | 4,900 | 4,900 | 4,900 |
| 200 | 3,060 | 4,570 | 4,900 | 4,900 | 4,900 | 4,900 |
| 205 | 3,000 | 4,490 | 4,900 | 4,900 | 4,900 | 4,900 |
| 210 | 2,950 | 4,410 | 4,900 | 4,900 | 4,900 | 4,900 |
| 215 | 2,890 | 4,330 | 4,900 | 4,900 | 4,900 | 4,900 |
| 220 | 2,840 | 4,260 | 4,900 | 4,900 | 4,900 | 4,900 |
| 225 | 2,790 | 4,180 | 4,900 | 4,900 | 4,900 | 4,900 |
| 230 | 2,750 | 4,110 | 4,900 | 4,900 | 4,900 | 4,900 |
| 235 | 2,700 | 4,040 | 4,900 | 4,900 | 4,900 | 4,900 |
| 240 | 2,660 | 3,980 | 4,900 | 4,900 | 4,900 | 4,900 |
| 245 | 2,610 | 3,910 | 4,900 | 4,900 | 4,900 | 4,900 |
| 250 | 2,570 | 3,850 | 4,900 | 4,900 | 4,900 | 4,900 |
| 255 | 2,530 | 3,790 | 4,900 | 4,900 | 4,900 | 4,900 |
| 260 | 2,490 | 3,730 | 4,900 | 4,900 | 4,900 | 4,900 |
| 265 | 2,460 | 3,680 | 4,900 | 4,900 | 4,900 | 4,900 |
| 270 | 2,420 | 3,620 | 4,900 | 4,900 | 4,900 | 4,900 |
| 275 | 2,380 | 3,570 | 4,900 | 4,900 | 4,900 | 4,900 |
| 280 | 2,350 | 3,520 | 4,900 | 4,900 | 4,900 | 4,900 |
| 285 | 2,320 | 3,470 | 4,900 | 4,900 | 4,900 | 4,900 |
| 290 | 2,280 | 3,420 | 4,900 | 4,900 | 4,900 | 4,900 |
| 295 | 2,250 | 3,370 | 4,900 | 4,900 | 4,900 | 4,900 |
| 300 | 2,220 | 3,330 | 4,900 | 4,900 | 4,900 | 4,900 |
| 許容支圧荷重(kN/m) | 9,800 | 14,700 | 22,050 | 29,400 | 29,400 | 29,400 |

※なお、部はデッキプレート型枠の最大製作可能長さ4.9mにより決定する箇所を示す。

JF100M許容スパン表 (S造)

軽量コンクリート1種

鉄筋コンクリート単重 $\rho = \boxed{20}$ (kN/m³)

| スラブ厚 S (mm) | 許 容 ス パ ン : L (mm) | | | | | |
|----------------------------|--------------------|-----------|-----------|-----------|-----------|-----------|
| | JF100M-07 | JF100M-08 | JF100M-10 | JF100M-12 | JF100M-14 | JF100M-16 |
| | Z= | 37.3 | 42.6 | 46.6 | 56.2 | 65.9 |
| I= | 250 | 284 | 352 | 417 | 482 | 545 |
| 120 | 3,360 | 3,880 | 4,140 | 4,460 | 4,660 | 4,830 |
| 125 | 3,360 | 3,850 | 4,110 | 4,430 | 4,620 | 4,800 |
| 130 | 3,360 | 3,820 | 4,070 | 4,400 | 4,590 | 4,760 |
| 135 | 3,360 | 3,790 | 4,040 | 4,360 | 4,560 | 4,730 |
| 140 | 3,360 | 3,760 | 4,020 | 4,330 | 4,530 | 4,690 |
| 145 | 3,360 | 3,740 | 3,990 | 4,300 | 4,490 | 4,660 |
| 150 | 3,360 | 3,710 | 3,960 | 4,270 | 4,460 | 4,630 |
| 155 | 3,360 | 3,690 | 3,930 | 4,250 | 4,430 | 4,600 |
| 160 | 3,360 | 3,660 | 3,910 | 4,220 | 4,410 | 4,570 |
| 165 | 3,360 | 3,640 | 3,880 | 4,190 | 4,380 | 4,540 |
| 170 | 3,360 | 3,620 | 3,860 | 4,170 | 4,350 | 4,510 |
| 175 | 3,360 | 3,590 | 3,840 | 4,140 | 4,320 | 4,490 |
| 180 | 3,360 | 3,570 | 3,810 | 4,120 | 4,300 | 4,460 |
| 185 | 3,340 | 3,550 | 3,790 | 4,090 | 4,270 | 4,430 |
| 190 | 3,320 | 3,530 | 3,770 | 4,070 | 4,250 | 4,410 |
| 195 | 3,300 | 3,510 | 3,750 | 4,040 | 4,230 | 4,380 |
| 200 | 3,280 | 3,490 | 3,730 | 4,020 | 4,200 | 4,360 |
| 205 | 3,260 | 3,470 | 3,710 | 4,000 | 4,180 | 4,340 |
| 210 | 3,250 | 3,450 | 3,690 | 3,980 | 4,160 | 4,310 |
| 215 | 3,230 | 3,440 | 3,670 | 3,960 | 4,130 | 4,290 |
| 220 | 3,210 | 3,420 | 3,650 | 3,940 | 4,110 | 4,270 |
| 225 | 3,200 | 3,400 | 3,630 | 3,920 | 4,090 | 4,250 |
| 230 | 3,180 | 3,380 | 3,610 | 3,900 | 4,070 | 4,230 |
| 235 | 3,160 | 3,370 | 3,590 | 3,880 | 4,050 | 4,200 |
| 240 | 3,150 | 3,350 | 3,580 | 3,860 | 4,030 | 4,180 |
| 245 | 3,130 | 3,330 | 3,560 | 3,840 | 4,010 | 4,160 |
| 250 | 3,120 | 3,320 | 3,540 | 3,820 | 3,990 | 4,140 |
| 255 | 3,100 | 3,300 | 3,520 | 3,810 | 3,980 | 4,130 |
| 260 | 3,090 | 3,290 | 3,510 | 3,790 | 3,960 | 4,110 |
| 265 | 3,080 | 3,270 | 3,490 | 3,770 | 3,940 | 4,090 |
| 270 | 3,060 | 3,260 | 3,480 | 3,750 | 3,920 | 4,070 |
| 275 | 3,050 | 3,240 | 3,460 | 3,740 | 3,910 | 4,050 |
| 280 | 3,040 | 3,230 | 3,450 | 3,720 | 3,890 | 4,040 |
| 285 | 3,020 | 3,220 | 3,430 | 3,710 | 3,870 | 4,020 |
| 290 | 3,010 | 3,200 | 3,420 | 3,690 | 3,860 | 4,000 |
| 295 | 3,000 | 3,190 | 3,400 | 3,670 | 3,840 | 3,990 |
| 300 | 2,980 | 3,180 | 3,380 | 3,660 | 3,820 | 3,970 |
| 重量(Z12)[N/m ²] | 133 | 151 | 188 | 223 | 258 | 294 |

| | | |
|--------|-------|--------------------|
| ヤング係数; | 205 | kN/mm ² |
| 撓み係数; | 180 | |
| 施工荷重; | 1,470 | N/m ² |
| 許容応力; | 235 | N/mm ² |

※なお、 部はたわみで決定する箇所を示す。

※赤文字部は、計算に依らず、デッキの最大スパンを示す。

JF100M中間サポート使用許容スパン表 (S造)

軽量コンクリート1種

鉄筋コンクリート単重 $\rho = 20$ (kN/m³)

| スラブ厚 S (mm) | 許 容 ス パ ン : L (mm) | | | | | |
|----------------|--------------------|-----------|-----------|-----------|-----------|-----------|
| | JF100M-07 | JF100M-08 | JF100M-10 | JF100M-12 | JF100M-14 | JF100M-16 |
| | Z= | I= | Z= | I= | Z= | I= |
| | 37.3 | 42.6 | 46.6 | 56.2 | 65.9 | 75.6 |
| | 250 | 284 | 352 | 417 | 482 | 545 |
| 120 | 4,890 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 125 | 4,770 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 130 | 4,660 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 135 | 4,550 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 140 | 4,450 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 145 | 4,350 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 150 | 4,250 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 155 | 4,160 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 160 | 4,080 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 165 | 3,990 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 170 | 3,910 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 175 | 3,840 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 180 | 3,760 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 185 | 3,690 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 190 | 3,620 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 195 | 3,560 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 200 | 3,490 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 205 | 3,430 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 210 | 3,370 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 215 | 3,320 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 220 | 3,260 | 4,880 | 4,900 | 4,900 | 4,900 | 4,900 |
| 225 | 3,210 | 4,800 | 4,900 | 4,900 | 4,900 | 4,900 |
| 230 | 3,150 | 4,720 | 4,900 | 4,900 | 4,900 | 4,900 |
| 235 | 3,100 | 4,650 | 4,900 | 4,900 | 4,900 | 4,900 |
| 240 | 3,060 | 4,570 | 4,900 | 4,900 | 4,900 | 4,900 |
| 245 | 3,010 | 4,500 | 4,900 | 4,900 | 4,900 | 4,900 |
| 250 | 2,960 | 4,440 | 4,900 | 4,900 | 4,900 | 4,900 |
| 255 | 2,920 | 4,370 | 4,900 | 4,900 | 4,900 | 4,900 |
| 260 | 2,880 | 4,310 | 4,900 | 4,900 | 4,900 | 4,900 |
| 265 | 2,830 | 4,240 | 4,900 | 4,900 | 4,900 | 4,900 |
| 270 | 2,790 | 4,180 | 4,900 | 4,900 | 4,900 | 4,900 |
| 275 | 2,750 | 4,120 | 4,900 | 4,900 | 4,900 | 4,900 |
| 280 | 2,720 | 4,070 | 4,900 | 4,900 | 4,900 | 4,900 |
| 285 | 2,680 | 4,010 | 4,900 | 4,900 | 4,900 | 4,900 |
| 290 | 2,640 | 3,960 | 4,900 | 4,900 | 4,900 | 4,900 |
| 295 | 2,610 | 3,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 300 | 2,570 | 3,850 | 4,900 | 4,900 | 4,900 | 4,900 |
| 許容支圧荷重(kN/m) | 9,800 | 14,700 | 22,050 | 29,400 | 29,400 | 29,400 |

※なお、部はデッキプレート型枠の最大製作可能長さ4.9mにより決定する箇所を示す。

JF100M許容スパン表 (S造)

軽量コンクリート2種

鉄筋コンクリート単重 $\rho = 18$ (kN/m³)

| スラブ厚 S (mm) | 許 容 ス パ ン : L (mm) | | | | | | |
|----------------------------|--------------------|-----------|-----------|-----------|-----------|-----------|-------|
| | JF100M-07 | JF100M-08 | JF100M-10 | JF100M-12 | JF100M-14 | JF100M-16 | |
| | Z= | 42.6 | 46.6 | 56.2 | 65.9 | 75.6 | |
| | I= | 250 | 284 | 352 | 417 | 482 | 545 |
| 120 | | 3,360 | 3,950 | 4,220 | 4,550 | 4,750 | 4,900 |
| 125 | | 3,360 | 3,920 | 4,190 | 4,520 | 4,720 | 4,890 |
| 130 | | 3,360 | 3,900 | 4,160 | 4,480 | 4,680 | 4,850 |
| 135 | | 3,360 | 3,870 | 4,130 | 4,450 | 4,650 | 4,820 |
| 140 | | 3,360 | 3,840 | 4,100 | 4,420 | 4,620 | 4,790 |
| 145 | | 3,360 | 3,820 | 4,070 | 4,390 | 4,590 | 4,760 |
| 150 | | 3,360 | 3,790 | 4,040 | 4,360 | 4,560 | 4,730 |
| 155 | | 3,360 | 3,770 | 4,020 | 4,340 | 4,530 | 4,700 |
| 160 | | 3,360 | 3,740 | 3,990 | 4,310 | 4,500 | 4,670 |
| 165 | | 3,360 | 3,720 | 3,970 | 4,280 | 4,470 | 4,640 |
| 170 | | 3,360 | 3,700 | 3,950 | 4,260 | 4,450 | 4,610 |
| 175 | | 3,360 | 3,680 | 3,920 | 4,230 | 4,420 | 4,580 |
| 180 | | 3,360 | 3,650 | 3,900 | 4,210 | 4,390 | 4,560 |
| 185 | | 3,360 | 3,630 | 3,880 | 4,180 | 4,370 | 4,530 |
| 190 | | 3,360 | 3,610 | 3,860 | 4,160 | 4,350 | 4,510 |
| 195 | | 3,360 | 3,590 | 3,830 | 4,140 | 4,320 | 4,480 |
| 200 | | 3,360 | 3,570 | 3,810 | 4,120 | 4,300 | 4,460 |
| 205 | | 3,340 | 3,550 | 3,790 | 4,090 | 4,280 | 4,440 |
| 210 | | 3,320 | 3,540 | 3,770 | 4,070 | 4,250 | 4,410 |
| 215 | | 3,310 | 3,520 | 3,750 | 4,050 | 4,230 | 4,390 |
| 220 | | 3,290 | 3,500 | 3,730 | 4,030 | 4,210 | 4,370 |
| 225 | | 3,270 | 3,480 | 3,720 | 4,010 | 4,190 | 4,350 |
| 230 | | 3,260 | 3,460 | 3,700 | 3,990 | 4,170 | 4,330 |
| 235 | | 3,240 | 3,450 | 3,680 | 3,970 | 4,150 | 4,310 |
| 240 | | 3,230 | 3,430 | 3,660 | 3,950 | 4,130 | 4,290 |
| 245 | | 3,210 | 3,420 | 3,650 | 3,940 | 4,110 | 4,270 |
| 250 | | 3,200 | 3,400 | 3,630 | 3,920 | 4,090 | 4,250 |
| 255 | | 3,180 | 3,380 | 3,610 | 3,900 | 4,070 | 4,230 |
| 260 | | 3,170 | 3,370 | 3,600 | 3,880 | 4,060 | 4,210 |
| 265 | | 3,150 | 3,350 | 3,580 | 3,870 | 4,040 | 4,190 |
| 270 | | 3,140 | 3,340 | 3,560 | 3,850 | 4,020 | 4,170 |
| 275 | | 3,130 | 3,330 | 3,550 | 3,830 | 4,000 | 4,150 |
| 280 | | 3,110 | 3,310 | 3,530 | 3,820 | 3,990 | 4,140 |
| 285 | | 3,100 | 3,300 | 3,520 | 3,800 | 3,970 | 4,120 |
| 290 | | 3,090 | 3,280 | 3,510 | 3,780 | 3,950 | 4,100 |
| 295 | | 3,070 | 3,270 | 3,490 | 3,770 | 3,940 | 4,090 |
| 300 | | 3,060 | 3,260 | 3,480 | 3,750 | 3,920 | 4,070 |
| 重量(Z12)[N/m ²] | | 133 | 151 | 188 | 223 | 258 | 294 |

| | | |
|--------|-------|--------------------|
| ヤング係数; | 205 | kN/mm ² |
| 撓み係数; | 180 | |
| 施工荷重; | 1,470 | N/m ² |
| 許容応力; | 235 | N/mm ² |

※なお、 部はたわみで決定する箇所を示す。
 ※赤文字部は、計算に依らず、デッキの最大スパンを示す。

JF100M中間サポート使用許容スパン表 (S造)

軽量コンクリート2種

鉄筋コンクリート単重 $\rho = 18$ (kN/m³)

| スラブ厚 S (mm) | 許 容 ス パ ン : L (mm) | | | | | |
|----------------|--------------------|-----------|-----------|-----------|-----------|-----------|
| | JF100M-07 | JF100M-08 | JF100M-10 | JF100M-12 | JF100M-14 | JF100M-16 |
| | Z= | I= | | | | |
| | 37.3 | 42.6 | 46.6 | 56.2 | 65.9 | 75.6 |
| | 250 | 284 | 352 | 417 | 482 | 545 |
| 120 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 125 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 130 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 135 | 4,850 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 140 | 4,750 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 145 | 4,650 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 150 | 4,550 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 155 | 4,460 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 160 | 4,370 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 165 | 4,280 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 170 | 4,200 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 175 | 4,120 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 180 | 4,040 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 185 | 3,970 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 190 | 3,900 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 195 | 3,830 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 200 | 3,760 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 205 | 3,700 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 210 | 3,640 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 215 | 3,580 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 220 | 3,520 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 225 | 3,460 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 230 | 3,410 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 235 | 3,360 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 240 | 3,300 | 4,900 | 4,900 | 4,900 | 4,900 | 4,900 |
| 245 | 3,250 | 4,870 | 4,900 | 4,900 | 4,900 | 4,900 |
| 250 | 3,210 | 4,800 | 4,900 | 4,900 | 4,900 | 4,900 |
| 255 | 3,160 | 4,730 | 4,900 | 4,900 | 4,900 | 4,900 |
| 260 | 3,110 | 4,660 | 4,900 | 4,900 | 4,900 | 4,900 |
| 265 | 3,070 | 4,600 | 4,900 | 4,900 | 4,900 | 4,900 |
| 270 | 3,030 | 4,530 | 4,900 | 4,900 | 4,900 | 4,900 |
| 275 | 2,990 | 4,470 | 4,900 | 4,900 | 4,900 | 4,900 |
| 280 | 2,950 | 4,410 | 4,900 | 4,900 | 4,900 | 4,900 |
| 285 | 2,910 | 4,350 | 4,900 | 4,900 | 4,900 | 4,900 |
| 290 | 2,870 | 4,290 | 4,900 | 4,900 | 4,900 | 4,900 |
| 295 | 2,830 | 4,240 | 4,900 | 4,900 | 4,900 | 4,900 |
| 300 | 2,790 | 4,180 | 4,900 | 4,900 | 4,900 | 4,900 |
| 許容支圧荷重(kN/m) | 9,800 | 14,700 | 22,050 | 29,400 | 29,400 | 29,400 |

※なお、部はデッキプレート型枠の最大製作可能長さ4.9mにより決定する箇所を示す。